

NOVATECH[®]

+ POSITIVE PRINTING

- The best bulk of the market combined with a velvety surface. Novatech Ultimatt quality ensures outstanding printability and runnability.
- Applications: annual reports, direct marketing, school books, fine books, magazines and catalogues.



NOVATECH ULTIMATT

PARAMETER	Standard	Unit											
BASIS WEIGHT	ISO 536	g/m ²	90	100	115	135	150	170	200	250	300	350	400
SPEC. VOLUME	ISO 534	cm ³ /g	1,05	1,05	1,05	1,05	1,05	1,05	1,05	0,90	0,94	0,99	1,03
THICKNESS	ISO 534	µm	95	105	121	142	158	179	210	225	282	347	412
BRIGHTNESS (Illuminant D65/10°)	ISO 2470-2	%	100	100	100	100	100	100	100	99	99	99	99
CIE WHITENESS (D65/10°)	ISO 11475	%	124	125	126	126	126	126	126	125	125	125	125
ROUGHNESS PPS	ISO 8791-4	µm	4.0	4.0	4.0	4.0	4.0	4.0	4.0	1.6	1.8	2.0	2.1
OPACITY	ISO 2471	%	94	95	96	97	98	98	99	98.5	99	99.5	99.5
RELATIVE HUMIDITY	TAPPI 502	%	50	50	50	50	50	50	50	50	50	50	50
PH VALUE	ISO 6588	-	>7	>7	>7	>7	>7	>7	>7	>7	>7	>7	>7
GLOSS TAPPI 75°	ISO 8254-1	%	14	14	14	14	14	14	14	17	17	17	17

These values are to be considered only as indications and are subject to change according to trade tolerances in the quality specification
Issue Date: September 2013

Packing and range options

Environmental certification

Suitable for

Applications and guarantees

